

## Warning horn WH/BL-24-98

### DESCRIPTION

Combined warning horn and flashlight in stable plastic housing (ABS) according to VDI 2053

### APPLICATION

All-purpose audio warning hooter with integrated xenon flashlight for acoustic and optical warning with separate actuation

### FEATURES

- Simple maintenance
- Continuous operation
- Long life-time
- Reliable

### TYPES

Combination of warning horn/ flashlight 24 V DC **WH/BL-24- 98**



### SPECIFICATIONS

#### Electrical

Power supply	18 – 30 V DC
Power consumption	Max. 68 mA
Audio frequency	32 arbitrary sounds, incl. DIN tone
Acoustic pressure	Max.100 dB (A)

#### Operating Environment

Humidity	0 - 95% RH non-condensing
Working temperature	-10 °C to + 55 °C
Storage temperature	-10 °C to + 55 °C
Pressure range	Atmospheric ±10%

#### Physical characteristics

Enclosure material	Thermoplastic (ABS), shock-resistant
Enclosure colour	Red
Dimensions (d x H)	Ca. 93 x 93 mm
Weight	0,32 kg
Protection class	IP 54
Mounting	Wall and ceiling installation
Cable entry	Ca.12 mm diameter
Wire connection	Screw-type terminals, min. 0.28 mm <sup>2</sup> , max. 2.5 mm <sup>2</sup>

#### Directives

VdS