

## Warning horn WH230/24

### DESCRIPTION

Warning horn in stable plastic housing (ABS) according to VDI 2053

### APPLICATION

All-purpose audio warning hooter with 32 adjustable sounds, incl. DIN tone for fire-detection and safety systems in accordance with the VdS directives.

### FEATURES

- Simple maintenance
- Continuous operation
- Long life-time
- Reliable



### TYPES

Warning horn 230 V AC, 98 dB	<b>WH-230-98</b>
Warning horn 230 V AC, 108 dB	<b>WH-230-108</b>
Warning horn 24 V DC, 98 dB	<b>WH-24-98</b>
Warning horn 24 V DC, 108 dB	<b>WH-24-108</b>

### SPECIFICATIONS

<b>Electrical</b>	
Power supply	110-240 V AC, 50 Hz or 9-28 V DC
Power consumption	Max. 35mA
Audio frequency	32 arbitrary sounds, incl. DIN tone
Acoustic pressure	64 dB(A) – 111 dB(A)
<b>Operating Environment</b>	
Humidity	0 - 95% RH non-condensing
Working temperature	-10 °C to + 55 °C
Storage temperature	-10 °C to + 55 °C
Pressure range	Atmospheric ±10%
<b>Physical characteristics</b>	
Enclosure material	Thermoplastics (ABS), shock-resistant
Enclosure colour	Red
Dimensions (d x H)	Ca. 93 x 93 mm
Weight	0,32 kg
Protection class	IP 54
Mounting	Wall and ceiling installation
Cable entry	Ca.12 mm diameter
Wire connection	Screw-type terminals, min. 0.28 mm <sup>2</sup> , max. 2.5 mm <sup>2</sup>
<b>Directives</b>	VdS